

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 1 of 13

SAFETY DATA SHEET

SECTION 1	IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING
------------------	---

As of the revision date above, this SDS meets the regulations in the United Kingdom excluding Northern Ireland.

1.1. PRODUCT IDENTIFIER

Product Name: ESCORENE™ ULTRA HEVA

Product Description: Ethylene Vinyl Acetate (EVA) Copolymer, see Section 16 for applicable grades.

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Intended Use: Adhesive component, Asphalt additive, Coatings, Compounding, Film, Molding

Uses advised against: None unless specified elsewhere in this SDS.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier: ExxonMobil Petroleum & Chemical BV
Polderdijkweg
B-2030 Antwerpen
Belgium
Phone: +32 3 790 31 11

Local Contact: ExxonMobil Chemical Ltd.

MAILPOINT 14
MARSH LANE
FAWLEY, SOUTHAMPTON
SO45 1TX HAMPSHIRE
Great Britain

Supplier General Contact:

E-Mail:

(UK) (+44) (0) 23 8089 3822

sds.uk@exxonmobil.com

1.4. EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Telephone:

National Poison Control Centre:

+44-870-820-04-18 (CHEMTREC)

(UK) 111

SECTION 2	HAZARDS IDENTIFICATION
------------------	-------------------------------

2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

Classification according to CLP

Not Classified

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 2 of 13

2.2. LABEL ELEMENTS

Label elements according to CLP

Hazard Statements:

Supplemental:

EUH210: Safety data sheet available on request.

2.3. OTHER HAZARDS

Physical / Chemical Hazards:

WARNING: May form combustible dust concentrations in air (during processing/handling). Thermal burn hazard - contact with hot material may cause thermal burns. Material can accumulate static charges which may cause an ignition. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Spilled pellets present a slipping hazard on hard surfaces.

Health Hazards:

If dust is generated, it could scratch the eyes and cause minor irritation to the respiratory tract. When heated, the vapour/fumes given off may cause respiratory tract irritation.

Environmental Hazards:

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1. SUBSTANCES Not Applicable. This material is regulated as a mixture.

3.2. MIXTURES

This material is defined as a mixture.

Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

Name	CAS#	EC#	Registration#	Concentration *	GHS/CLP classification
Vinyl Acetate	108-05-4	203-545-4	01-2119471301-50	0.1 - < 1.0%	[Acute Tox. 5 H303], Acute Tox. 4 H332, Carc. 2 H351, Flam. Liq. 2 H225, STOT SE 3 H335, [Aquatic Acute 3 H402], Aquatic Chronic 3 H412, Note D

Note - any classification in brackets is a GHS building block that was not adopted in CLP and therefore is not applicable in the countries which have implemented CLP and is shown for informational purposes only.

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 3 of 13

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note: See SDS Section 16 for full text of hazard statements.

SECTION 4 FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

INHALATION

In case of adverse exposure to vapours and / or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. For hot product: Immediately immerse in or flush affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention.

EYE CONTACT

Flush thoroughly with water for at least 15 minutes. Get medical assistance.

INGESTION

Seek immediate medical attention.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

No important symptoms or effects.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

The need to have special means for providing specific and immediate medical treatment available in the workplace is not expected.

SECTION 5 FIRE FIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Acetic acid, Flammable hydrocarbons, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Vinyl acetate

5.3. ADVICE FOR FIRE FIGHTERS

Fire Fighting Instructions: Assure an extended cooling down period to prevent re-ignition. Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Product Name: ESCORENE™ ULTRA HEVA

Revision Date: 23 Nov 2021

Revision Number: 3.00

Page 4 of 13

Unusual Fire Hazards: Explosion: Avoid generating dust; fine dust dispersed in air in sufficient concentration and in the presence of an ignition source is a potential dust explosion hazard.

FLAMMABILITY PROPERTIES

Flash Point [Method]: Not technically feasible

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available

Autoignition Temperature: Not technically feasible

SECTION 6

ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (for example, clearing dust surfaces with compressed air). Prevent dust exposure to ignition sources. For example, use non-sparking tools and prohibit smoking, flares, sparks or flames in immediate area. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

6.2. ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Land Spill: Spilled pellets present a slipping hazard on hard surfaces. Prevent dust cloud. Small Dry Spills: With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

SECTION 7

HANDLING AND STORAGE

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 5 of 13

7.1. PRECAUTIONS FOR SAFE HANDLING

Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dust from material can accumulate electrostatic charges due to friction from transfer and mixing operations and cause an electrical spark (ignition source). Provide adequate precautions to ignition sources, such as electrical grounding and bonding, inert atmosphere or non-sparking tools. However, bonding and grounds may not eliminate the hazard for static accumulation. Consult local applicable standards for guidance. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids and EN 61241, Electrical Apparatus for Use in the Presence of Combustible Dust for safe handling. Avoid elevated temperatures for prolonged periods of time. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Avoid all personal contact. Prevent small spills and leakage to avoid slip hazard. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Care should be taken when storing and handling this product. Apart from the specific nature of the polymer product, conditions such as humidity, sunlight and temperature have an influence on the way the product behaves during storage and handling. Special attention should be paid to avoid inappropriate stacking of palletised bags or other package units. Indeed, polymer products may be dimensionally unstable under certain conditions. Avoid conditions generating heat during transfer operations.

Loading/Unloading Temperature: [Ambient]

Transport Temperature: [Ambient]

Transport Pressure: [Ambient]

Static Accumulator: This material is a static accumulator.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

Storage Temperature: [Ambient]

Storage Pressure: [Ambient]

Suitable Containers/Packing: Bulk Containers; Drums; Bags; Hopper Cars; Octatainer; Silos

Suitable Materials and Coatings (Chemical Compatibility): Aluminium; Plastic Coatings

7.3. SPECIFIC END USES

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Standard	Note	Source
Vinyl Acetate		STEL 15 ppm		ACGIH

UK EH40 Workplace Exposure Limits. Exposure limits for use with Control of Substances Hazardous to Health Regulations 2002 (as amended)

Product Name: ESCORENE™ ULTRA HEVA

Revision Date: 23 Nov 2021

Revision Number: 3.00

Page 6 of 13

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

UK Health and Safety Executive (HSE)

8.2. EXPOSURE CONTROLS

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded. **SPECIAL PRECAUTIONS:** Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures (for example, oxygenated components). Processors of this product should assure that adequate ventilation or other controls are used to control exposure. It is recommended that the current ACGIH-TLVs for thermal degradation by-products be observed. Contact your local sales representative for further information. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product are designed and maintained to minimize dust generation and accumulation. Ensure that dust-handling systems (such as exhaust ducts, dusts collectors, vessels, and processing equipment) are designed to minimize the potential for dust ignition and prevent explosion propagation. For example, use explosion relief vents, an explosion suppression system or inert equipment internals. Additional examples of proper equipment include using only appropriately classified electrical equipment and powered industrial trucks.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Particulate air-purifying respirator approved for dust or oil mist is recommended. European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If product is hot, thermally protective, chemical

Product Name: ESCORENE™ ULTRA HEVA

Revision Date: 23 Nov 2021

Revision Number: 3.00

Page 7 of 13

resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves. CEN standards EN 420 and EN 374 provide general requirements and lists of glove types.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended. If product is hot, thermally protective, chemical resistant apron and long sleeves are recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid

Form: Pellet

Colour: Clear to Opaque, White to Off-White

Odour: Mild Sour/Acidic

Odour Threshold: No data available

pH: Not technically feasible

Melting Point: 35°C (95°F) - 110°C (230°F) [In-house method]

Freezing Point: Not technically feasible

Initial Boiling Point / and Boiling Range: Not technically feasible

Flash Point [Method]: Not technically feasible

Evaporation Rate (n-butyl acetate = 1): Not technically feasible

Flammability (Solid, Gas): Not technically feasible

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available

Vapour Pressure: Not technically feasible

Vapour Density (Air = 1): Not technically feasible

Relative Density (at 15.6 °C): 0.91 - 0.97 [In-house method]

Solubility(ies): water Negligible

Partition coefficient (n-Octanol/Water Partition Coefficient): Not technically feasible

Autoignition Temperature: Not technically feasible

Decomposition Temperature: No data available

Viscosity: Not technically feasible

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 8 of 13

Explosive Properties: None
Oxidizing Properties: None

9.2. OTHER INFORMATION

Bulk Density: 4 g/cc at 20 °C - 1 g/cc at 20 °C [In-house method]
Density (at 15 °C): 910 kg/m3 (7.59 lbs/gal, 0.91 kg/dm3) - 970 kg/m3 (8.09 lbs/gal, 0.97 kg/dm3) [In-house method]
Molecular Weight: 700 - 50000
Hygroscopic: No

SECTION 10 STABILITY AND REACTIVITY

10.1. REACTIVITY: See sub-sections below.

10.2. CHEMICAL STABILITY: Material is stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

10.4. CONDITIONS TO AVOID: Excessive heat. Avoid elevated temperatures for prolonged periods of time.

10.5. INCOMPATIBLE MATERIALS: Fluorine, Strong oxidisers

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on chemical structure (polymers).
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on chemical structure (polymers).
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on chemical structure (polymers).
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on chemical structure (polymers).
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on chemical structure (polymers).
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on chemical structure (polymers).

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 9 of 13

Aspiration: No end point data for material.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Based on chemical structure (polymers).
Carcinogenicity: No end point data for material.	Contains a substance that may cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Not expected to be a reproductive toxicant. Based on chemical structure (polymers).
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on chemical structure (polymers).

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
Vinyl Acetate	Inhalation Lethality: 4 hour(s) LC50 15.8 mg/l (Vapour) (Rat); Oral Lethality: LD 50 3470 mg/kg (Rat)

OTHER INFORMATION

For the product itself:

Elevated temperatures or mechanical action may form vapours, mists or fumes which may be irritating to the eyes and respiratory tract.

Dust may be irritating to eyes and respiratory tract.

Contains:

Additives that are encapsulated in the polymer. Under the normal conditions for processing and use of this polymer the encapsulated additives are not expected to pose any health hazard. However, grinding of the polymer is not recommended without the use of appropriate measures to control exposure (see Section 8 - Engineering Controls).

Vinyl acetate monomer. Vinyl acetate has been shown to be carcinogenic in rodents when administered at very high concentrations via the inhalation and oral routes of exposure. Tumors were observed in tissues that directly contact vinyl acetate, i.e., the nose and upper respiratory tract following inhalation or the oral cavity/upper digestive tract following ingestion. Research on the mechanism of nasal and upper digestive tract tumor induction suggests that these carcinogenic effects are not expected to occur in humans exposed to low concentrations via occupational or environmental pathways.

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

12.1. TOXICITY

Material -- Not expected to be harmful to aquatic organisms.

Material -- Not expected to be harmful to terrestrial organisms.

12.2. PERSISTENCE AND DEGRADABILITY

Biodegradation:

Material -- Expected to be persistent.

Hydrolysis:

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 10 of 13

Material -- Transformation due to hydrolysis not expected to be significant.

Photolysis:

Material -- Transformation due to photolysis not expected to be significant.

Atmospheric Oxidation:

Material -- Transformation due to atmospheric oxidation not expected to be significant.

12.3. BIOACCUMULATIVE POTENTIAL

Material -- Potential to bioaccumulate is low.

12.4. MOBILITY IN SOIL

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

13.1. WASTE TREATMENT METHODS

Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

The European Waste Catalogue (EWC) / List of Waste (LoW) code is specific to the waste generating process and waste constituents. Determine the EWC / LoW according to the criteria provided in the European Waste Catalogue and the hazardous waste list established by Commission Decision 2000/532/EC or the UK List of Waste, as amended.

SECTION 14	TRANSPORT INFORMATION
-------------------	------------------------------

LAND (ADR/RID): 14.1-14.6 Not Regulated for Land Transport

INLAND WATERWAYS (ADN): 14.1-14.6 Not Regulated for Inland Waterways Transport

SEA (IMDG): 14.1-14.6 Not Regulated for Sea Transport according to IMDG-Code

SEA (MARPOL 73/78 Convention - Annex II):

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not classified according to Annex II

Product Name: ESCORENE™ ULTRA HEVA
Revision Date: 23 Nov 2021
Revision Number: 3.00
Page 11 of 13

AIR (IATA): 14.1-14.6 Not Regulated for Air Transport

SECTION 15	REGULATORY INFORMATION
-------------------	-------------------------------

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories : Please contact Customer Service (see Section 1 for supplier contact information).

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Applicable UK legislation:

REACH [... Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto]
CLP [Classification, labelling and packaging of substances and mixtures.. and amendments thereto]

REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII):

The following entries of Annex XVII may be considered for this product: None

15.2. CHEMICAL SAFETY ASSESSMENT

REACH Information: A Chemical Safety Assessment has been carried out for one or more substances present in the material.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

REFERENCES: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AIIC	Australian Inventory of Industrial Chemicals
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)

Product Name: ESCORENE™ ULTRA HEVA

Revision Date: 23 Nov 2021

Revision Number: 3.00

Page 12 of 13

DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration
EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

Flam. Liq. 2 H225: Highly flammable liquid and vapor; Flammable Liquid, Cat 2

[Acute Tox. 5 H303]: May be harmful if swallowed; Acute Tox Oral, Cat 5

Acute Tox. 4 H332: Harmful if inhaled; Acute Tox Inh, Cat 4

STOT SE 3 H335: May cause respiratory irritation; Target Organ Single, Resp Irr

Carc. 2 H351: Suspected of causing cancer; GHS Carcinogenicity, Cat 2

[Aquatic Acute 3 H402]: Harmful to aquatic life; Acute Env Tox, Cat 3

Aquatic Chronic 3 H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Section 08: Exposure Limits Table information was modified.

THIS SDS COVERS THE FOLLOWING MATERIALS: Escorene™ Ultra EVA resins: | FL 00014 | FL 00018 | FL 00112 | FL 00119 | FL 00206 | FL 00209 | FL 00212 | FL 00218 | FL 00309 | FL 00328 | FL 00623 | FL 00714 | FL 00909 | FL 01418 | FL 02020 | POLY 101 | UL 00014 | UL 00018 | UL 00112 | UL 00114 | UL 00119 | UL 00218CC3 | UL 00328 | UL 00514 | UL 00728 | UL 02020 | UL 02133EN2 | UL 04331EL | UL 15019CC | UL 53019CC | Including Experimental grades beginning with EX

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Product Name: ESCORENE™ ULTRA HEVA

Revision Date: 23 Nov 2021

Revision Number: 3.00

Page 13 of 13

Internal Use Only

MHC: 0, 0, 0, 0, 0, 0

DGN: 4408971KGB (1014249)

This product is not classified for human health and environmental hazards, and an exposure scenario is not required. This SDS conveys the appropriate risk management measures.

ANNEX

Annex not required for this material.