

Company: Polyram Plastic Industries Ltd.
Company Address: Ram-on 19205 ISRAEL
Print Date: 28 Mar 2018



RAMCLEAN® 600

Purging Agent, Any temperature

Product Description:

RAMCLEAN 600: Very effective purging agent, Non-Corrosive, Non-Abrasive and Non-Toxic designed to clean a variety of resins being processed concurrently, a situation that may occur in multi-layer, multi-resin sheet and film extrusion lines. Great for PE film and any other material within working temperatures of 120°C –280°C.

This product is food contact standards compliant.

Product Information:

Characteristic	Unit	Test method	Property value
Physical properties			
Bulk Density	Kg/lit	INTERNAL	1.3
Determination of ASH	%	ISO 3451-1	15
Moisture Content(ppm)	ppm	INTERNAL	<1500

Regulations:

SVHC: SVHC Compliance

ROHS2: ROHS Compliance

EU 10/2011: Monomer and additives are listed as authorized monomers/additives In Annex I of regulations (EC) No. 10/2011.

EU 10/2011: Monomer and additives are listed as authorized monomers/additives In Annex I of regulations (EC) No. 10/2011.

FDA: Conform to FDA CFR 21 for indirect food contact

Conflict Minerals

Conflict Minerals

Revision #1

Revision Date: 12 Nov 2017

The technical data contained herein are guides to use Polyram resins. Information contained herein is to the best knowledge, true and assure. The customer is nevertheless obliged to run an incoming material control.