

# High Density Polyethylene

## H8067B

### PRODUCT DESCRIPTION

HDPE injection homopolymer for general injection molding application.

### APPLICATIONS

Product used for general injection molding application, including crates, totes, and bins. Without UV.

### TYPICAL PROPERTIES

Properties	Typical Value	Unit	Test Method
Melt Flow Index (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Density	0.965	g/cm <sup>3</sup>	ASTM D1505

**DISCLAIMER:** THIS TECHNICAL DATA SHEET SHOWS THE TYPICAL PROPERTIES AND THE DATA SHOW ARE NOT TO BE CONSTRUED AS SPECIFICATIONS. THE DOCUMENT IS DESIGNED TO PROVIDE USERS GENERAL INFORMATION AND DOES NOT CONSITUTE ANY WARRANTY OR QUALITY SPECIFICATION, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. USERS SHALL DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR USE AND CAN BE USED SAFELY AND LEGALLY.