

# Linear Low Density Polyethylene

**LL1019B6****PRODUCT DESCRIPTION**

LLDPE hexene resin for general packaging application.

**APPLICATIONS**

Product used for general packaging, including cast film.

**ADDITIVE**

Product is without additives (No Antiblock/No Slip)

Properties	Typical Value	Unit	Test Method
Melt Flow Index (190°C/2.16 kg)	1.0	g/10 min	ASTM D1238
Density	0.918	g/cm <sup>3</sup>	ASTM D792

\* These are typical properties.

**ADDITIVE**

Antiblock	None
Slip	None
Other	None

**DISCLAIMER:** THIS TECHNICAL DATA SHEET SHOWS THE TYPICAL PROPERTIES AND THE DATA SHOWN ARE NOT TO BE CONSTRUED AS SPECIFICATIONS. THE DOCUMENT IS DESIGNED TO PROVIDE USERS GENERAL INFORMATION AND DOES NOT CONSTITUTE ANY WARRANTY OR QUALITY SPECIFICATION, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. USERS SHALL DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR USE AND CAN BE USED SAFELY AND LEGALLY.