

# Linear Low Density Polyethylene

**LL1118B****PRODUCT DESCRIPTION**

LLDPE resin for general packaging application. Prime resin with FDA certification. Under development resin.

**APPLICATIONS**

Product used for general film extrusion for packaging, including industrial liners and trash bags.

**TYPICAL PROPERTIES**

Properties	Typical Value	Unit	Test Method
Melt Flow Index (190°C/2.16 kg)	0.9 - 1.1	g/10 min	ASTM D1238
Density	0.918 - 0.919	g/cm <sup>3</sup>	ASTM D792

**ADDITIVE**

Antiblock	None
Slip	None
Other	Thermal Stabilizer

**DISCLAIMER:** THIS TECHNICAL DATA SHEET SHOWS THE TYPICAL PROPERTIES AND THE DATA SHOW ARE NOT TO BE CONSTRUED AS SPECIFICATIONS. THE DOCUMENT IS DESIGNED TO PROVIDE USERS GENERAL INFORMATION AND DOES NOT CONSITUTE ANY WARRANTY OR QUALITY SPECIFICATION, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. USERS SHALL DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR USE AND CAN BE USED SAFELY AND LEGALLY.