

Linear Low Density Polyethylene

LL2022B**PRODUCT DESCRIPTION**

LLDPE resin for general packaging application.

APPLICATIONS

Product used for general packaging, including cast film.

ADDITIVE

Product is without additives (No Antiblock/No Slip)

Properties	Typical Value	Unit	Test Method
Melt Flow Index (190°C/2.16 kg)	2.0	g/10 min	ASTM D1238
Density	0.918 - 0.919	g/cm ³	D1505

* These are typical properties.

ADDITIVE

Antiblock	None
Slip	None
Other	None

DISCLAIMER: THIS TECHNICAL DATA SHEET SHOWS THE TYPICAL PROPERTIES AND THE DATA SHOWN ARE NOT TO BE CONSTRUED AS SPECIFICATIONS. THE DOCUMENT IS DESIGNED TO PROVIDE USERS GENERAL INFORMATION AND DOES NOT CONSTITUTE ANY WARRANTY OR QUALITY SPECIFICATION, EITHER EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. USERS SHALL DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR USE AND CAN BE USED SAFELY AND LEGALLY.