

Version: 102

Plastribution Ltd

A l'attention de
For the attention of Daniel Jarvis

**CERTIFICAT DE SPECIFICATIONS
CERTIFICATE OF SPECIFICATIONS**

SIEGE SOCIAL
HEAD OFFICE

Rue de l'industrie 52 Nijverheidsstraat
1040 Bruxelles – Belgique

Total Polyethylene Lumicene® mPE M 2310 EP

CARACTERISTIQUES CHARACTERISTICS	UNITE UNIT	MOYENNE AVERAGE	TOLERANCE TOLERANCE	NORME STANDARD
INDICE DE FLUIDITE/MELT INDEX 190°C-2.16 KG	g/10min	0,9	0.65 - 1.15	EN ISO 1133
DENSITE/DENSITY A 23 ° C	g/cm ³	0,9225	0.9205 - 0.9245	ISO 1183

Les spécifications indiquées sont valables au maximum 3 ans à partir de la date indiquée.
These specifications will be valid for a maximum of 3 years from the date of this document.

Date: 06 juillet 2020

Christian PENU
Flexible Packaging & Personal Care Manager

The content of this specification is confidential and cannot be disclosed to third parties without the agreement of TOTAL RESEARCH & TECHNOLOGY FELUY. This document remains valid for a 3-year-period from the date of issue. In case TOTAL RESEARCH & TECHNOLOGY FELUY, within the period, makes any changes to the product that could affect the above specification; notice will be given.